

# GÖLZ®



**Hand-Held Power Tools  
for Diamond Tool Operation**

[www.golzgroup.com](http://www.golzgroup.com)

**Robust and powerful - perfect for small grinding and polishing requirements.**

**Easy polishing - grinding - cleaning**

**Perfect surface preparation**

**Features**

- Softstart and surface speed control
- Thermal overload protection shown by LED lights
- 125 mm dust collector cover, front can be opened to operate direct against a wall
- 35 mm vacuum hose connector
- Handles adjustable for your comfort
- Carrying case inclusive



Specifications	GÖLZ SM125
Motor	230 V, 50 - 60 Hz
Power	1,8 kW
RPM	10.000 min <sup>-1</sup>
Cup Grinder Ø	125 mm
Arbor hole Ø	22,23 mm
Soft-Start	yes
Protection class	2
Weight	5,4 kg
<b>Order number</b>	<b>SM 125</b>

Accessories	Order number
Dry Vac Vibra 125	0284 810 3000

**Powerful Wall Chaser - Designed for your safety and comfort.**

Operates 2 diamond blades up to a max. cutting width of 46 mm and a max. cutting depth of 45 mm.

**Quick and easy to use in**

- Sandstone
- Soft bricks
- Poroton
- Hard bricks
- Limestone
- Clinker
- Concrete

**Features**

- Softstart electronic
- Thermal overload protection
- Overload LED lights
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector
- Carrying case inclusive

**Advantages**

- Cuts 15mm close to a wall
- Ergonomical Handles
- Easy handling
- Steppless cutting depth adjustment
- Easy handling by big switches and buttons
- Almost dust free



Specifications	GÖLZ SF150
Operation	Dry only
Motor	230 V, 50 Hz
Power	2,3 kW
RPM	4.300 min <sup>-1</sup>
max. Blade Ø	150 mm
Arbor hole Ø	22,23 mm
Max cutting depth	45 mm
Max cutting width	46 mm
Weight	5,8 kg
<b>Order number (without diamondblade)</b>	<b>SF 150</b>

Accessories	Order number
Dry Vac Vibra 125	0284 810 3000

# Electric Cut Off Saw ES350

**Electrical Cut Off Saw for wet and dry operation - Vac-adaptor for slurry and dust control - the allround saw for most of your sawing requirements up to a cutting depth of 130 mm (5 inch)**

Powerful 2,7 kW Electric-Cut Off Saw - 350 mm (14 inch) blade and blade guard with integrated vac-adaptor. The anti-clockwise rotating blade guarantees best dust and slurry control by connecting a vacuum cleaner.

#### Quick and easy to use in

- All kinds of openings in concrete or brick walls
- Cutting pipes, concrete, stone, clinker and brick

#### Features

- 2,7 kW electric motor with soft start electronic
- Thermal overload protection
- Easy cutting depth adjustment
- Easy tool change
- 35 mm vacuum hose connector
- Adjustable blade guard and handles
- Easy to operate by extra wide guiding wheels



Specifications	GÖLZ ES350
Operation	Dry and Wet
Motor	230 V, 50 Hz
Power	2,7 kW
RPM	2.200 min <sup>-1</sup>
max. Blade Ø	350 mm
Arbor hole Ø	25,4 mm
Max cutting depth	130 mm
Weight	12,5 kg
Order number	0295 150 1300

Accessories	Order number
Cutting depth limiter	0295 150 1310
Close to wall cutting adapter	0295 150 1311

## Hand Held Core Drilling Machines



## Single Speed Dry Drilling Hand Held Core Drill. Dry drilling with and without dust collection for switches and junction boxes

- Single speed drill for holes up to 160 mm
- No vibrations, no impact drilling
- Dry drilling in soft bricks, blocks and poroton, porous concrete, sand-lime bricks
- Thermal overload protection
- Accessories: Dry core bits, Dust collector, see Diamond tools catalogue (page 29)
- Carrying Case inclusive



Specifications	GÖLZ TB10S
Operation	Dry
Style	D-handle
Motor	Single phase, 230 V, 50 Hz
Power	1,8 kW (1,2 kW)
RPM	1200 min <sup>-1</sup>
Gears	1
Bit-ø in Brickwork (Dry)	Ø up to 160 mm
Drill bit connection	M18 male
Water connection	---
Ring collar Ø	53 mm
Dimensions (LxWxH)	460x95x320 mm
Weight	5,7 kg
<b>Order number</b>	<b>0295 007 6050</b>

## 2-Speed Heavy Duty Hand Held Core Drill. Compact Core Drill for anchor and installation holes

- 2-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2" (FB23) or R1/2" (FB25)
- PRCD integrated in the power cord
- Softstart and thermal overload protection
- FB23S/FB23P - wet & dry use up to Ø 200 mm
- FB25P- wet use, up to Ø 70 mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive
- Carrying Case inclusive



Specifications	GÖLZ FB23S	GÖLZ FB23P	GÖLZ FB25P
Operation	Wet & Dry		Wet
Style	D-handle	Pistol-handle	
Motor	Single phase, 230 V, 50 Hz		
Power	2,2 kW (1,5 kW)		
RPM	520/1400 min <sup>-1</sup>		1400/2900 min <sup>-1</sup>
Gears	2		
Bit-ø in Concrete (Wet)	10 - 110 mm – Hand held 10 - 200 mm – Stand mounted	10 - 70 mm - Hand held 10 - 70 mm - Stand mounted	
Bit-ø in Brickwork (Dry)	20 - 200 mm - Hand held, (Optional dust collector)		
Drill bit connection	1 1/4"UNC + R 1/2"		R 1/2"
Water connection	Gardena		
Ring collar Ø	60 mm		
Dimensions (LxWxH)	547x150x100 mm	396x100x295 mm	337x100x295 mm
Weight	5,9 kg	5,9 kg	5,6 kg
<b>Order number</b>	<b>0295 007 5063</b>	<b>0295 007 5020</b>	<b>0295 007 5025</b>

Accessories	Order number
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000



## 3-Speed Heavy Duty Hand Held Core Drill. Powerful core drill is full in metal housing for hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Softstart and thermal overload protection
- Wet & dry use up to Ø 200mm
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive
- Carrying Case inclusive



Specifications	GÖLZ FB33PNT	GÖLZ FB33SNT
Operation	Wet & Dry	
Style	Pistol-handle	D-handle
Motor	Single phase, 230 V, 50 Hz	
Power	2,2 kW (1,5 kW)	
RPM	520/1400/2900 min <sup>-1</sup>	
Gears	3	
Bit-Ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 200 mm - Stand mounted	
Bit-Ø in Brickwork (Dry)	20 - 200 mm - Hand held Dust collector integrated	
Drill bit connection	1 1/4" UNC + R1/2"	
Water connection	Geka-coupling / Gardena	
Ring collar Ø	60 mm	
Dimensions (LxWxH)	440x100x285 mm	562x100x150 mm
Weight	6,5 kg	
Order number	0295 007 5082	0295 007 5065

Accessories	Order number
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000



## 3-Speed Hand Held Core Drill. For hand held or drill stand operation

- 3-Speed Gearbox
- Drill Bit connection 1 1/4" UNC + R 1/2"
- PRCD integrated in the power cord
- Thermal overload protection
- Wet & Dry use in Concrete and Brickwork
- Horizontal & Vertical Bubble Levels
- Toolset SW32 & SW41 inclusive



Specifications	GÖLZ FB20P
Operation	Wet & Dry
Style	Pistol-handle
Motor	Single phase, 230 V, 50 Hz
Power	2,2 kW (1,5 kW)
RPM	450/1200/2500 min <sup>-1</sup>
Gears	3
Bit-Ø in Concrete (Wet)	20 - 110 mm - Hand held 20 - 200 mm - Stand mounted
Bit-Ø in Brickwork (Dry)	20 - 200 mm - Hand held
Drill bit connection	1 1/4" UNC + R1/2"
Water connection	Gardena
Ring collar Ø	60 mm
Dimensions (LxWxH)	432 x 119 x 272 mm
Weight	6,7 kg
Order number	0295 007 5080

Accessories	Order number
Carrying Case	B802223
Drill Stand DS160S (up to Ø 162 mm)	0295 110 9010
Drill Stand KB125 (up to Ø 200 mm)	0295 125 6000





# **GÖLZ® - Group**

## **GÖLZ GmbH**

**Dommersbach 51 | 53940 Hellenthal  
Telefon +49 2482 12-0 | Fax +49 2482 12-222  
info@goelz.de | www.goelz.de**

### **ÖSTERREICH**

**Gölz Ges.m.b.H.  
Samstr. 52 | A-5020 Salzburg  
Telefon +43 662 438175 | Fax +43 662 430734  
info@goelz.at | www.goelz.at**

### **FRANKREICH**

**Gölz S.A.S.  
1, rue de la Mairie | F-67370 Berstett  
Telefon +33 3 88 59 43 00 | Fax +33 3 88 59 47 77  
info@golz.fr | www.golz.fr**

### **GROSSBRITANNIEN**

**Golz (UK) Ltd.  
Unit A5 | Springhead, Enterprise Park  
Northfleet | Kent DA 11 8HB  
Telefon +44 1 474 321 679 | Fax +44 1 474 321 477  
info@goelz.co.uk | www.golzuk.com**

### **BENELUX**

**Gölz Benelux N.V. Belgien  
Eupener Straße 61 | B-4731 Raeren-Eynatten  
Telefon +32 87 55 23 49 | Fax +32 13 78 33 28  
benelux@goelz.de | www.golzgroup.com**

### **USA**

**Golz L.L.C.  
5860 East Osage Ridge Lane | Columbia MO 65203-6018  
info@golzusa.com | www.golzgroup.com**



**Your GÖLZ dealer**

